



## Continous Monitor Selection Guide

### Personal Grounding & Work Surface Grounding



Product Name	Mini Monitor	Multi-Mount Monitor	Dual Operator Monitor	Full Time Monitor
Part #	19341, 19343	19336, 19337	19655, 19656	19330, 19331
Technology	Impedance	Impedance	Impedance	Impedance
Operator(s)	1	1	2	1
Work Surfaces	1	1	1	1
Park Snap Delay Switch	Yes	Yes	Yes	Yes
Power Relay Compatible	No	No	Yes	Yes
Light Tower Compatible	No	Yes	No	Yes
Access Control	No	No	No	Yes
AC Outlet Monitoring	No	No	No	Yes
Body Voltage Monitoring	No	No	No	No
Operator Test Range	500 kilohms - 10 megohms (impedance)			
Operator Test Voltage	1.2 V peak-to-peak @ 1.2 $\mu$ A, open circuit	1.2 V peak-to-peak @ 1.2 $\mu$ A, open circuit	1.2 V peak-to-peak @ 1.2 $\mu$ A, open circuit	1.2 V peak-to-peak @ 1.2 $\mu$ A, open circuit
Alarm Response Time	< 50 milliseconds	< 50 milliseconds	< 500 milliseconds	< 500 milliseconds
Power Supply	9V DC	9V DC	9V DC	9V DC
Cable Length	5 ft.	5 ft.	5 ft.	6 ft.
Calibration	98221 Verification Tester	98221 Verification Tester	98221 Verification Tester	98221 Verification Tester