

ELP Flex Printer



Three configurations with interchangeable print heads

203dpi • 300dpi • 600dpi



Standard Interfaces

- USB 2.0
- Ethernet
- Parallel
- 9-pin RS-232
- USB host for scanner or keyboard

Stand Alone Printing

Stand Alone Mode promotes cost savings by ease of use, freeing up valuable floor space and allowing diverse printer placement. No PC needed.

Available to quote today!
sales@identco.com
1 (800) 533-2559

Highlights

- Interchangeable printheads
- 1 printer = 3 printers (203-300-600dpi)
- Exceptional print registration
- ZPL Emulation - Best in the industry
- Large color LCD touch screen
- Minimal waste during calibration
- Easy loading and removal of labels/ribbons
- Direct-gear driven - no belts to wear out
- Stand alone printing mode.
- No PC needed. Very user friendly operation

Features

- Standard 600 meter ribbon lengths
- Up to 14" per second print speed
- Holds 8" OD media rolls
- Standard 1" core ribbons, CSO/CSI
- 2 year printer warranty
- Optional Cutter



www.identco.com

ELP™ Flex Printer

Interchangeable Print Heads



Labels for Life.

■ Standard □ Option

LABEL PRINTER

	Print method	Thermal transfer / Direct thermal		
Printhead	Print resolution dpi	203	300	600
	Print speed up to mm/s	356	254	102
	Print width mm	104	104	104
	Media roll total diameter up to mm	208	208	208
Material	Label width mm	25.4-116*	25.4-116*	25.4-116*
	Label length up to mm	25,400	11,430	2,540
	Ribbon Ink coated (1" cores)	CSO/CSI	CSO/CSI	CSO/CSI
Ribbon	Ribbon length variable up to m	600	600	600
	Ribbon width up to mm	114	114	114
	Print Alignment	Media is left (L) or center (C) justified	L	L
Dual Side Printing	Print on both sides of media	NO	NO	NO
Printer Dimensions	Width x Height x depth mm	270x308x515	270x308x515	270x308x515
	Weight (lbs.)	33	33	33
Electronics	Processor high speed clock rate MHz	32-bit RISC	32-bit RISC	32-bit RISC
	RAM MB	128	128	128
	Memory IFFS MB Flash	128	128	128
	ZPL emulation	YES	YES	YES
	Stand-Alone Printing	YES	YES	YES
	Slot for Compact Flash Memory Card	■	■	■
	Slot for wireless LAN card	RS-232	RS-232	RS-232
	Warning signal	Acoustic signal in case of error		
Interfaces	Centronics bi-directional acc. IEEE 1284	■	■	■
	RS-232 (9 pin)	■	■	■
	USB 2.0 High Speed for PC	■	■	■
	Ethernet 10/100 Base T	■	■	■
	USB host for scanner or keyboard	■	■	■
	Bluetooth	□	□	□
	WLAN card 802.11 b/g	□	□	□
Options	Cutter	□	□	□
	Peel-off kit	□	□	□

¹⁾ All materials are approximate values. Small labels, very thin, narrow, thick or stiff materials as well as labels with strong adhesives need to be tested first.



Note: All values shown are averages and should not be used for specification purposes. Test data and test results contained in this document are for general information only and shall not be relied upon by IDENTCO customers for designs and specifications, or be relied on as meeting specific performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact IDENTCO for further information. Revised 7/7/2017.

UNITED STATES HEADQUARTERS

28164 W. Concrete Drive
Ingleside, IL 60041
Phone: +1 (815) 385 - 0011
Fax +1 (815) 385 - 0359

MEXICO MONTERREY

Carr. a Laredo Km. 16.5 Interior
14B, Col. Moisés Sáenz, 66613
Apodaca, Nuevo Leon
Phone: +52 (81) 8008 - 0438

GERMANY FRANKFURT

Güterbahnhofstrasse 3-7
63450 Hanau
Phone: +49 (6181) 440 830 - 0
Fax: +49 (6181) 440 830 - 99

PRC HONG KONG

Unit 1708, 17/F, 9 Wing Hong St.
Cheung Sha Wan, Kowloon
Phone: +852 2959 2156
Fax: +852 2959 2019

MALAYSIA PENANG

Suite 163E, Level 16, Room 1602
Hunza Tower Gurney Paragon
Jalan Kelawei, Georgetown
10250 Penang
Phone: +6012 466 - 0866